

KEL-DPZ round Cable entry plates




IP66

IP68



Also available in black.



Membrane on front



Conical shape on back provides additional sealing and strain relief

Product description

2.1

KEL-DPZ entry plates are designed to route and seal cables without connectors or fibre optics (from 1.5 mm to 22 mm in diameter) in limited space.

The assembly of the KEL-DPZ round with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ round provides strain relief and protection IP66 / IP68 / UL type 4X.

The round versions of the KEL-DPZ series have a thread to fit in metric cut-outs from M25 to M63. Thus cut-outs for metric cable glands can be used.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

Type	Order No.	Number of cables	Thread metric	External diameter	Mounting height	PU
KEL-DPZ 25 3	43736 50736	2× 3.2 - 5.2 mm 1× 3.2 - 6.5 mm	M25 × 1.5	39 mm	8 mm	10
KEL-DPZ 25 4	43737 50737	4× 3.2 - 5.2 mm	M25 × 1.5	39 mm	8 mm	10
KEL-DPZ 32 4	43732 50732	3× 3.2 - 6.5 mm 1× 7.2 - 12.5 mm	M32 × 1.5	44 mm	8 mm	10
KEL-DPZ 32 4-2	43733 50733	4× 5 - 9.5 mm	M32 × 1.5	44 mm	8 mm	10
KEL-DPZ 32 7	43734 50734	7× 3.2 - 6.5 mm	M32 × 1.5	44 mm	8 mm	10
KEL-DPZ 40 8	43741 50741	4× 3.2 - 6.5 mm 4× 5 - 10.2 mm	M40 × 1.5	52 mm	8 mm	10
KEL-DPZ 50 8	43750 50750	5× 5 - 10.2 mm 3× 7.2 - 12.5 mm	M50 × 1.5	62 mm	8 mm	10
KEL-DPZ 50 10	43751 50751	7× 3.2 - 6.5 mm 2× 5 - 10.2 mm 1× 16 - 22.2 mm	M50 × 1.5	62 mm	8 mm	10
KEL-DPZ 50 12	43752 50752	4× 3.2 - 6.5 mm 8× 5 - 10.2 mm	M50 × 1.5	62 mm	8 mm	10

* Only valid for grey product types



KEL-DPZ 25