

KEL-DPZ round Cable entry plates



IP66

IP68

Type	Order No.	Number of cables	Thread metric	External diameter	Mounting height	PU
KEL-DPZ 50 19	43758 50758	19× 3.2 - 6.5 mm	M50 × 1.5	62 mm	8 mm	10
KEL-DPZ 50 78	43756 50756	76× 1.5 - 2.6 mm 2× 2.5 - 5 mm	M50 × 1.5	62 mm	8 mm	10
KEL-DPZ 63 9	43760 50760	1× 3.2 - 6.5 mm 3× 5 - 10.2 mm 4× 9 - 16.2 mm 1× 16 - 22.2 mm	M63 × 1.5	75 mm	8 mm	10
KEL-DPZ 63 13	43761 50761	4× 3.2 - 6.5 mm 4× 5 - 10.2 mm 5× 9 - 16.2 mm	M63 × 1.5	75 mm	8 mm	10
KEL-DPZ 63 14	43762 50762	14× 5 - 10.2 mm	M63 × 1.5	75 mm	8 mm	10
KEL-DPZ 63 35	43763 50763	35× 3.2 - 6.5 mm	M63 × 1.5	75 mm	8 mm	10

* Only valid for grey product types

Advantages & benefits

- Quick and easy tool-free assembly
- High cable density
- Automatic sealing and strain relief for the cable
- Suitable for metric cut-outs
- Polyamide locknuts are included in the shipment
- Dual sealing of cables acc. to IP66 /IP68 / up to UL type 4X
- Hygienic design - free of dirt-collecting recesses

Specifications

Material	Thread frame: Polyamide (PA)
Colour	Sealing plate: Elastomer grey (similar RAL 7035) black
Flame class	UL94-Vo, self-extinguishing
IP rating	IP66/IP67/IP68 (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E) UL type 4X (acc. to UL 50E)
Temperature	- 40°C to + 90°C (static)
Properties	Halogen-free, silicone-free
Cut-out dim.	Metric sizes
Thread length	14 mm
Plate depth	8 mm

Accessories

ST-B Plugs	85
FP Flanged plates	178 - 183
MP Module plates	174 - 175

2.1