

BIG series – Multiple cable entries

Hoods with 4 pegs

size **57.27**
**Heavy-Duty
Applications**


EN 60529	IP65 / IP66 / IP69
When coupled with V-TYPE series - IP67 version	IP65 / IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Hoods with 4 pegs, side and/or top entry, without gasket To be used only with a complete cable gland	Side entry	Top entry	
		MBO 10.40		
		MBO 10.50		
		Side and Top entries		
		MBVO 10.240	M40 M50 M40 × 2	
	Hoods with 4 pegs, designed to be drilled, without gasket	Without entry CBC 10		
	Hoods with 4 pegs, 2 x top entries, without gasket To be used only with a complete cable gland	MBV 10.225	M25 × 2	 MBV 10.225
	Hoods with 4 pegs, 4 x top entries, without gasket To be used only with a complete cable gland	MBV 10.420	M20 × 4	 MBV 10.420

Inserts size 57.27	Poles	Pages
CNE	16 A	10 + ☉ B.39
CCE	16 A	10 + ☉ B.45
CSH / JSH S	16 A	10 + ☉ B.53,59
CSHT	16 A	10 + ☉ B.66
CQE / CQEY	16 A	18 + ☉ B.73,83
CDD	10 A	42 + ☉ B.95
CDSH	10 A	18 + ☉ B.103
CSS	16 A	10 + ☉ B.119

Inserts size 57.27	Poles	Pages
CMCE / CMSH	16 A	3 + 2 (aux.) + ☉ B.144,149
CX	40 A/10 A	8/24 + ☉ B.170-171
MIXO Modular Inserts		Pages
MIXO modules		C.12-93
CX 03 T (3-slot sized MIXO frames)		C.95

Complete with:


**V-TYPE
Housings**
Page E.125