

# E-Xtreme® – C-TYPE lever version

size **77.27**

Hoods and covers – 4 pegs – without gasket

**2 000 hrs resistance**  
in salt-spray tests







**Aggressive**  
Environments


|                            |                    |
|----------------------------|--------------------|
| EN 60529                   | IP65 / IP66 / IP69 |
| UL 50 / UL 50E             | Type 12 / 4 / 4X   |
| Ambient temperature limits | -40 °C ... +125 °C |
| Mechanical life (cycles)   | ≥ 500              |

CE UK



ECBT2.E115072 | ECBT8.E115072

| Item                                                                                | Description                                                                                                                                                                                                                                                                                        | Side entry                                               | Top entry                                                | Entry      | Dimension                                                                             |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|----------------------------------------------------------|------------|---------------------------------------------------------------------------------------|
|    | Hoods, 4 pegs, side entry, high construction                                                                                                                                                                                                                                                       | <a href="#">MHOE 16.25</a><br><a href="#">MHOE 16.32</a> |                                                          | M25<br>M32 |    |
|    | Hoods, 4 pegs, top entry, high construction<br><br>To be used only with a complete cable gland                                                                                                                                                                                                     |                                                          | <a href="#">MHVE 16.25</a><br><a href="#">MHVE 16.32</a> | M25<br>M32 |   |
|   | Hoods, 4 pegs, side or top entry, high construction<br><br>To be used only with a complete cable gland                                                                                                                                                                                             | <a href="#">MFOE 16.32</a><br><a href="#">MFOE 16.40</a> | <a href="#">MFVE 16.32</a><br><a href="#">MFVE 16.40</a> | M32<br>M40 |  |
|  | Covers, 4 pegs<br><br>For enclosures with 2 levers and gasket<br><br>with loop for hoods <br>or<br>with eyelet for housings  | With loop<br><br><a href="#">CHCE 16</a>                 | With eyelet<br><br><a href="#">CHCE 16 S</a>             |            |  |

E-Xtreme®

E

| Inserts size 77.27 | Poles  | Pages   | Inserts size 77.27 | Poles                         | Pages              | MIXO Modular Inserts               | Pages   |
|--------------------|--------|---------|--------------------|-------------------------------|--------------------|------------------------------------|---------|
| CNE 16 A           | 16 + ⊕ | B.40    | CP / CPY 35 A      | 6 + ⊕                         | B.112,114          | MIXO modules                       | C.12-93 |
| CCE 16 A           | 16 + ⊕ | B.46    | CSS 16 A           | 16 + ⊕                        | B.120              | CX 04 T (4-slot sized MIXO frames) | C.95    |
| CSH / JSH S 16 A   | 16 + ⊕ | B.54,60 | CMCE / CMSH 16 A   | 6 + 2 (aux.) + ⊕              | B.145,150          |                                    |         |
| CSHT 16 A          | 16 + ⊕ | B.67    | CX / CXC 80 A/16 A | 4/0, 4/2 + ⊕                  | B.158-160          |                                    |         |
| CQE / CQEY 16 A    | 32 + ⊕ | B.74,84 |                    |                               |                    |                                    |         |
| CQEE 16 A          | 40 + ⊕ | B.78    | CX 40 A/10 A       | 6/12, 6/36, 9/42 and 12/2 + ⊕ | B.163-164, 168-169 |                                    |         |
| CD 10 A            | 40 + ⊕ | B.90    |                    |                               |                    |                                    |         |
| CDD 10 A           | 72 + ⊕ | B.94    |                    |                               |                    |                                    |         |
| CDSH 10 A          | 27 + ⊕ | B.104   |                    |                               |                    |                                    |         |

## Accessories:


**CHCP 16**  
Dust protection  
cover  
Page G.46