

180 °C series – Heat shield enclosures

size **77.27**

Hoods and covers – 4 pegs – without gasket






Specialized
Applications

CE UK

BUREAU
DNV VERITAS

EN 60529	IP65
UL 50 / UL 50E	Type 12 / 4
Ambient temperature limits	-40 °C ... +180 °C
Mechanical life (cycles)	≥ 500

cALUS ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 4 pegs, without gasket, side entry	MHOR 16.25		M25	
	Hoods, 4 pegs, without gasket, top entry		MHVR 16.25	M25	
	Hoods, 4 pegs, without gasket, side or top entry, high construction	MFOR 16.40	MFVR 16.40	M40	
	Hoods, 4 pegs, without gasket, high construction, designed to be drilled	Without entry			
	Cover, 4 pegs, without gasket For enclosures with 2 levers and gasket with eyelet for housings 	Cover	CHCR 16		

Inserts size 77.27	Poles	Pages
CNE RY	16 A	16 + ☉ I.7
CP RY	35 A	6 + ☉ I.10
CX RY	80 A	4 + ☉ I.11
CX RY	80A / 16 A	4/2 + ☉ I.12