

C-TYPE series

Hoods – 4 pegs – without gasket

size **57.27**
**Heavy-Duty
Applications**











CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 4 pegs, without gasket, side entry	MHO 10.20 MHO 10.25 CHO 10		M20 M25 Pg 16	 
	Hoods, 4 pegs, without gasket, top entry To be used only with a complete cable gland		MHV 10.20 MHV 10.25 CHV 10	M20 M25 Pg 16	 
	Hoods, 4 pegs, without gasket, side or top entry, high construction To be used only with a complete cable gland	MFO 10.32 MFO 10.40 CFO 10.21 CFO 10.29	MFV 10.32 MFV 10.40 CFV 10.21 CFV 10.29	M32 M40 Pg 21 Pg 29	 
	Hoods, 4 pegs, without gasket, high construction, designed to be drilled	Without entry CAC 10			 

C-TYPE

E

Inserts size 57.27	Poles	Pages	Inserts size 57.27	Poles	Pages
CNE	16 A	10 + ☉ B.39	CMCE / CMSH	16 A	3 + 2 (aux.) + ☉ B.144,149
CCE	16 A	10 + ☉ B.45	CX	40 A/10 A	8/24 + ☉ B.170-171
CSH / JSH S	16 A	10 + ☉ B.53,59			
CSHT	16 A	10 + ☉ B.66			
CQE / CQEY	16 A	18 + ☉ B.73,83			
CDD	10 A	42 + ☉ B.95			
CDSH	10 A	18 + ☉ B.103			
CSS	16 A	10 + ☉ B.119			
			MIXO Modular Inserts		Pages
			MIXO modules		C.12-93
			CX 03 T (3-slot sized MIXO frames)		C.95

Accessories:


CHCP 10
Dust protection
cover
Page G.46