

C-TYPE series

Hoods – 2 pegs – without gasket

size **77.27**
**Heavy-Duty
Applications**










CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 pegs, without gasket, side entry	MHO 16 L25 MHO 16 L32 CHO 16 L		M25 M32 Pg 21	 
	Hoods, 2 pegs, without gasket, top entry To be used only with a complete cable gland		MHV 16 L25 MHV 16 L32 CHV 16 L	M25 M32 Pg 21	 
	Hoods, 2 pegs, without gasket, side or top entry, high construction To be used only with a complete cable gland	MFO 16 L32 MFO 16 L40 CFO 16 L21 CFO 16 L29	MFV 16 L32 MFV 16 L40 CFV 16 L21 CFV 16 L29	M32 M40 Pg 21 Pg 29	 
	Hoods, 2 pegs, without gasket, high construction, designed to be drilled	Without entry CAC 16 L			 

C-TYPE

E

Inserts size 77.27	Poles	Pages	Inserts size 77.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	16 + ⊕	B.40	CP / CPY 35 A	6 + ⊕	B.112,114	MIXO modules	C.12-93
CCE 16 A	16 + ⊕	B.46	CSS 16 A	16 + ⊕	B.120	CX 04 T (4-slot sized MIXO frames)	C.95
CSH / JSH S 16 A	16 + ⊕	B.54,60	CMCE / CMSH 16 A	6 + 2 (aux.) + ⊕	B.145,150		
CSHT 16 A	16 + ⊕	B.67	CX / CXC 80 A/16 A	4/0, 4/2 + ⊕	B.158-160		
CQE / CQEY 16 A	32 + ⊕	B.74,84					
CQEE 16 A	40 + ⊕	B.78	CX 40 A/10 A	6/12, 6/36, 9/42 and 12/2 + ⊕	B.163-164, 168-169		
CD 10 A	40 + ⊕	B.90					
CDD 10 A	72 + ⊕	B.94					
CDSH 10 A	27 + ⊕	B.104					

Accessories:

CHCP 16
Dust protection
cover
Page G.46