

Slim enclosures with C-TYPE lever




size **66.40**

Hoods and covers – 4 pegs

**Heavy-Duty
Applications**


EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500


ALUS ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 4 pegs without gasket, side entry	MHO 50.25 MHO 50.32 CHO 50		M25 M32 Pg 21	
	Hoods, 4 pegs without gasket, side or top entry, high construction To be used only with a complete cable gland	MFO 50.25 MFO 50.32 CFO 50.21 CFO 50.29	MFV 50.25 MFV 50.32 CFV 50.21 CFV 50.29	M25 M32 Pg 21 Pg 29	
	Hoods, 4 pegs without gasket, high construction, designed to be drilled	Without entry CAC 50			
	Covers, 4 pegs, without gasket For enclosures with 2 levers and gasket with loop for hoods  or with eyelet for housings 	With loop CHC 50 S	With eyelet CHC 50		

Inserts size (66.16) × 2	Poles	Pages
CDA 16 A	32 + ⊕	B.18
CDC 16 A	32 + ⊕	B.21
CSAH 16 A	32 + ⊕	B.26
CD 10 A	50 + ⊕	B.32
CDD 10 A	76 + ⊕	B.34