

E-Xtreme® – IP68 high protection version

size **44.27**

Housings, hoods and covers – Screw locking

3 000 hrs resistance
in salt-spray tests

Aggressive Environments








EN 60529	IP66 / IP68 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
with silicone gasket (on request)	-60 °C ... +125 °C*
Mechanical life (cycles)	≥ 500

*(>125 °C up to 180 °C with RY inserts)

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, screw locking Optional mounting frame CG .. FL is available to ensure water tightness for bulkhead mounting housing when fitted onto a cabinet panel. (See page G.45)	CGIE 06		
	Surface mounting housings, screw locking	MGPE 06.32	M32	
	Hoods, side entry, screw locking	MGOE 06.25 MGOE 06.32	M25 M32	
	Hoods, top entry, screw locking	MGVE 06.25 MGVE 06.32 MGVE 06.40	M25 M32 M40	
	Covers, screw locking, for housings With loop 	CGCE 06		

Inserts size 44.27	Poles	Pages
CNE	16 A 6 + ⊕	B.38
CCE	16 A 6 + ⊕	B.44
CSH / JSH S	16 A 6 + ⊕	B.52,58
CQE / CQEY	16 A 10 + ⊕	B.72,82
CDD	10 A 24 + ⊕	B.94
CDSH / CDSH NC	10 A 9 and 6 + ⊕	B.102,108
CSS	16 A 6 + ⊕	B.118
CT / CTSE*	16 A 6 + ⊕	B.126,130

*can be used only in bulkhead mounting housings

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 02 T (2-slot sized MIXO frames)	C.95

180 °C Inserts size 44.27	Poles	Pages
CNE RY** 16 A	6 + ⊕	I.5

** >125 °C up to 180 °C

Accessories:


CGCP FX
Dust protection
cover
Page G.47

CGCP MB
Dust protection
cover
Page G.47