



IP68 high protection – CGK / MGK

size **21.21**

Housings and hoods – Bayonet locking

Aggressive Environments

CE UK

EN 60529	IP66 / IP68 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, bayonet locking	CGK I B		
	Hoods, top entry, bayonet locking Not suitable for CQ4 series inserts	MGK V20 B CGK V13 B	M20 Pg 13,5	
	Hoods, top entry, bayonet locking	MGK V25 B	M25	

CGK / MGK

A

Compact 21.21 Inserts	Poles	Pages
CQ4 / CQ / CQY	40 A to 6,5 A	2 to 21 + ☉
CK / JK / CKSH	10 A	3 to 4 + ☉
CD / CDY	10 A	8
CJ (RJ45)	1 A to 2,1 A	–
CUK (USB)	–	–
CX (BUS)	10 A	–
CLK (Fibre optics)	–	–

Notes:
Eliminate the gasket and the fixing screw; provided with the insert. To fix the insert, use the screw with gasket provided with the enclosure.

Accessories:



CGKCP FX
Dust protection cover
Page G.47



CGKCP MB
Dust protection cover
Page G.47