

Special enclosures



Bulkhead connectors

size **44.27 – 104.27**

Heavy-Duty Applications

EN 60529	-
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

ECBT2.E115072 | ECBT8.E115072

Item	Description	Size	Part No.	Dimension
	Bulkhead mounting housings with 2 or 4 pegs 1) compatible only with V-Type lever and JEI® plastic lever enclosures 2) may be combined also with enclosures: - surface mounting housings - hoods with lever and gasket IP degrees are according to the type of lever of the counterpart enclosures. Panel cut-out drawings on page E.86.	44.27	CHI 06 LCH 1)	 <p>CHI 06 LCH</p>
		57.27	CHI 10 CH 2)	
		77.27	CHI 16 CH 2)	 <p>CHI 16 CH</p>
		104.27	CHI 24 CH 2)	

Inserts	Pages
CNE	B.38-43
CCE	B.44-49
CSH / JSH S	B.52-63
CSHT	B.66-68
CQE / CQEE	B.72-79
CQEY	B.82-87
CD	B.90-93
CDD	B.94-99
CDSH	B.102-107
CP / CPY	B.112-115
CSS	B.118-123
CT / CTSE, CT / CTS	B.126-135,138-141
CMCE / CMSH	B.144-153
CX / CXC	B.156-171
Frames for modular units	C.95

Complete with:



Enclosures with levers and gasket
 IL-BRID (Bulkhead, Surface, Hoods)
 Pages E.90-103

Enclosures with levers and gasket
 V-TYPE (Bulkhead, Surface, Hoods)
 Pages E.124-127,129,131,133,135