



CJK 8M

size **21.21**
1 seat for RJ45 connectors

Insulation resistance	≥ 10 GΩ
Ambient temperature limit	-40 °C ... +70 °C
Mechanical life (cycles)	≥ 500

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Dimension
	Universal patch cord adapter CR CJK G gasket supplied with universal patch cord adapter To be used with hoods with glued gasket, DESINA® version	CJK 8M	 Compatible patch cord dimensions
	RAL 7035 Plastic cable gland RAL 9005 Plastic cable gland IP65 degree of protection; for higher degree we recommend the use of ASR B25 gasket. The cable glands are compatible with the use of the CR CJK G gasket shown above.	AW M25IJ AW M25INJ	
	Nickel plated brass cable gland The cable gland is compatible with the use of the CR CJK G gasket shown above.	AW M25PJ	

Materials	
Insert	polycarbonate (PC)
UL 94 flame rating	V-0
Colour	white, RAL 7035



Tutorial



CR KC
Coding pins
Page G.11

Compact 21.21 enclosures	Pages
Heavy-Duty Applications	
Thermoplastic	A.46-48,51-52*
Thermoplastic with metal lever	A.53-55
Metallic	A.56-63,65-66*
Aggressive Environments	
Metallic IP68 high protection	A.78-81
Specialized Applications	
Hygienic series for food and beverage	A.94-96*

* male inserts without gasket compatible only with hoods with glued gasket, **DESINA®** version

Inserts already supplied with stainless steel fixing screw with gasket, which ensures IP66/IP67/IP69 degree of protection