

Metallic – CKA / MKA

Housings – 1 lever

size **21.21**Heavy-Duty
Applications

EN 60529	IP44
With CKR 65	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65	Type 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	With cover	Entry	Dimension
	Bulkhead mounting housings, 1 stainless steel lever, with or without self-closing cover	CKAX 03 I	For male inserts		
			For female inserts		
			CKAX 03 ILSA		
			CKAX 03 ILS		
	Angled bulkhead mounting housings, 1 stainless steel lever Not suitable for CQ4 series inserts	CKAX 03 IA			
	Angled bulkhead mounting housings, 1 stainless steel lever, with cable entry, open or closed bottom flange Not suitable for CQ4 series inserts	MKAX IAP20 CKAX 03 IAPS	Open bottom flange	M20 Pg 11	
			Closed bottom flange	M20 Pg 11	
		MKAX AP20 CKAX 03 APS			

Compact 21.21 Inserts	Poles	Pages
CQ4 / CQ / CQY	40 A to 6,5 A	A.4-12
CK / JK / CKSH	10 A	A.16-19
CD / CDY	10 A	A.24-25
CJ (RJ45)	1 A to 2,1 A	A.30-33
CUK (USB)	–	A.36
CX (BUS)	10 A	A.37
CLK (Fibre optics)	4	A.38

Note: to obtain the IP66 / IP67 / IP69 degree of protection it is necessary to replace the fixing screw supplied with all inserts, with the one with gasket included in the CKR 65 kit, to be purchased separately, except for the inserts listed below (already supplied with a fixing screw with gasket):

- CQF/M 07, CQF/M 12
- CJ KF
- CJK 8FT / 8IFT
- CUK 2FT / 3FT
- CX 1/2 BDF/M
- CLK 04 SCF / SCF-H / SCM

Accessories:



CKR 65
gasket and screw kits for
IP66 / IP67 / IP69
Page A.67