

Metallic – CKA / MKA

size **21.21**

Hoods and covers – 1 lever










**Heavy-Duty
Applications**


EN 60529	IP44
With CKR 65	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65	Type 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Hoods, 1 stainless steel lever, top entry Not suitable for CQ4 series inserts	MKAX VG20 CKAX 03 VGS	M20 Pg 11	
	Hoods, 1 stainless steel lever, top entry	MKAX VG25	M25	
 	Covers, 1 stainless steel lever, with or without gasket For hoods with 2 pegs with loop 	With gasket (for female inserts) CKAX 03 CX Without gasket (for male inserts) CKAX 03 CXA		  ◀ CKAX 03 CX CKAX 03 CXA ▶

Compact 21.21 Inserts	Poles	Pages
CQ4 / CQ / CQY	40 A to 6,5 A	A.4-12
CK / JK / CKSH	10 A	A.16-19
CD / CDY	10 A	A.24-25
CJ (RJ45)	1 A to 2,1 A	A.30-33
CUK (USB)	–	A.36
CX (BUS)	10 A	A.37
CLK (Fibre optics)	4	A.38

Note: to obtain the IP66 / IP67 / IP69 degree of protection it is necessary to replace the fixing screw supplied with all inserts, with the one with gasket included in the CKR 65 kit, to be purchased separately, except for the inserts listed below (already supplied with a fixing screw with gasket):

- CQF/M 07, CQF/M 12 - CUK 2FT /3FT
- CJ KF - CX 1/2 BDF/M
- CJK 8FT /8IFT - CLK 04 SCF /SCF-H /SCM

Accessories:



CKR 65
gasket and screw kits for
IP66 / IP67 / IP69
Page A.67