

CKM / CQAM

Termination connectors

EN 61984 rating









- CKM 03 T..	10 A	400 V	4 kV	3
- CQAM 12 T1	10 A	400 V	6 kV	3
	10 A	400 / 690 V	6 kV	2

EAC

BUREAU
DNV VERITAS

CIRIUS

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Dimension
	Termination connector for CKF and CKSHF 03 inserts With pegs and seal Connects pole 2 with pole 3	CKM 03 T1	  <ul style="list-style-type: none"> interconnected 2-3 poles
	Termination connector for CKF and CKSHF 03 inserts With pegs and seal Connects pole 1 with pole 2 When the termination connector is mated with a CK..F 03 insert (complete with enclosure with lever), it performs a dual function, to connects two socket insert poles and to acts as a cover (IP65 protection rating compliant with EN 60529 standard)	CKM 03 T3	  <ul style="list-style-type: none"> interconnected 1-2 poles
	Termination connector for CQF 12 inserts With pegs and seal Connects pole 5 with pole 6 and pole 7 with pole 8 When the termination connector is mated with a CQF 12 insert (complete with enclosure with lever), it performs a dual function, to connects two socket insert poles and to acts as a cover (IP65 protection rating compliant with EN 60529 standard) CR Q03 coding pins can be used with CQAM 12 T1 . In this case the CQF 12 inserts must be provided with CR Q12 coding pins	CQAM 12 T1	  <ul style="list-style-type: none"> interconnected 5-6/7-8 poles

Inserts	Pages
CKF 03	A.16
JKF 03	A.17
CKFD 03	A.18
CKSHF 03	A.19
CQF 12	A.11