

Thermoplastic – CKX / MKX

Housings – 1 metal lever

size **21.21**Heavy-Duty
Applications

EN 60529	IP44
With CKR 65	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65	Type 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Light grey	Jet black	Entry	Dimension
	Bulkhead mounting housings, 1 stainless steel lever	CKX 03 I	CKX 03 IN		
	Angled bulkhead mounting housings, 1 stainless steel lever Not suitable for CQ4 series inserts	CKX 03 IA			
	Angled bulkhead mounting housings, 1 stainless steel lever, fixing by 4 screws	CKX 03 IA4			
	Angled bulkhead mounting housings, 1 stainless steel lever, with open bottom flange, with cable entry, with or without cable gland Not suitable for CQ4 series inserts	With cable gland CKX 03 IAP Without cable gland CKX 03 IAPS		Pg 11 Pg 11	
	Angled bulkhead mounting housings, 1 stainless steel lever, with open bottom flange, M25 cable entry, fixing by 4 screws	MKX IAP25		M25	

Compact 21.21 Inserts	Poles	Pages
CQ4 / CQ / CQY	40 A to 6,5 A	A.4-12
CK / JK / CKSH	10 A	A.16-19
CD / CDY	10 A	A.22-23
CD / CDY	10 A	A.24-25
CJ (RJ45)	1 A to 2,1 A	A.30-33
CUK (USB)	–	A.36
CX (BUS)	10 A	A.37
CLK (Fibre optics)	–	A.38

Note: to obtain the IP66 / IP67 / IP69 degree of protection it is necessary to replace the fixing screw supplied with all inserts, with the one with gasket included in the CKR 65 kit, to be purchased separately, except for the inserts listed below (already supplied with a fixing screw with gasket):

- CQF/M 07, CQF/M 12
- CJ KF
- CJK 8FT /8IFT
- CUK 2FT /3FT
- CX 1/2 BDF/M
- CLK 04 SCF /SCF-H /SCM

Accessories:



CKR 65
gasket and screw kits for
IP66 / IP67 / IP69
Page A.67