













# CX..MPQ/MP

## Metal pneumatic contacts

Insulation resistance	$\geq 10 \text{ G}\Omega$
Ambient temperature limit	$-40 \text{ }^{\circ}\text{C} \dots +80 \text{ }^{\circ}\text{C}$
Mechanical life (cycles)	$\geq 500$

Item	Description	Part No.	Dimension
	Quick-fitting (outer Ø) male contacts, without shut-off valve, for tube Ø 8 mm without shut-off valve, for tube Ø 10 mm	straight <a href="#">CX 8.0 MPQM</a> <a href="#">CX 10 MPQM</a>	
	Quick-fitting (outer Ø) female contacts, without shut-off valve, for tube Ø 8 mm without shut-off valve, for tube Ø 10 mm	straight <a href="#">CX 8.0 MPQF</a> <a href="#">CX 10 MPQF</a>	
	Quick-fitting (outer Ø) female contacts, with shut-off valve, for tube Ø 8 mm with shut-off valve, for tube Ø 10 mm	straight <a href="#">CX 8.0 MPQV</a> <a href="#">CX 10 MPQV</a>	
	Hose barbs (inner Ø) male contacts, without shut-off valve, for tube Ø 8 mm without shut-off valve, for tube Ø 10 mm	straight <a href="#">CX 8.0 MPM</a> <a href="#">CX 10 MPM</a>	
	Hose barbs (inner Ø) female contacts, without shut-off valve, for tube Ø 8 mm without shut-off valve, for tube Ø 10 mm	straight <a href="#">CX 8.0 MPF</a> <a href="#">CX 10 MPF</a>	
	Hose barbs (inner Ø) female contacts, with shut-off valve, for tube Ø 8 mm with shut-off valve, for tube Ø 10 mm	straight <a href="#">CX 8.0 MPV</a> <a href="#">CX 10 MPV</a>	

### Materials

Contact	nickel plated brass
---------	---------------------