



# CYG

2,1 A 35 V<sub>AC</sub>/50 V<sub>DC</sub>

size **21.21**

2 seats for RJ45 connectors Cat. 5

EN 60529	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Rated voltage	35 V <sub>AC</sub> / 50 V <sub>DC</sub>
Rated current	2,1 A at 70 °C
Ambient temperature limit	-40 °C ... +120 °C

Item	Description	Part No.	Dimension
	RJ45 coupler jack, within insulating housings 4 data contacts* 4 data + 2 power contacts* 8 data contacts 8 data + 2 power contacts * on request	<a href="#">CYG 4 JF</a> <a href="#">CYG 4/2 JF</a> <a href="#">CYG 8 JF</a> <a href="#">CYG 8/2 JF</a>	
	RJ45 coupler jack, within metallic housings 4 data contacts* 4 data + 2 power contacts* 8 data contacts 8 data + 2 power contacts * on request	<a href="#">CYG 4 JFA</a> <a href="#">CYG 4/2 JFA</a> <a href="#">CYG 8 JFA</a> <a href="#">CYG 8/2 JFA</a>	

### Materials

Insert	polycarbonate (PC)
Shielding	nickel-plated brass
Insulating enclosure	self-extinguishing thermoplastic
Metal enclosure	die-cast zinc alloy
UL 94 flame rating	V-0
Insert colour	white, RAL 7035
Insulating enclosure colour	jet black, RAL 9005
Metal enclosure colour	grey, RAL 7040



**CR KC**  
Coding pins  
Page G.11

Accessories	Pages
CW J5..M Cat. 5 cable plug	A.34
CWC J5..M Cat. 5 cable plug	A.34