

V-TYPE series – IP67 version

Housings – 2 levers – with gasket

size **104.27**
**Heavy-Duty
Applications**


CE UK



EN 60529	IP65 / IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	With cover	Entry	Dimension
	Bulkhead mounting housings, 2 levers and gasket, with or without metal cover Optional mounting frame C7 .. FL is available to ensure water tightness for bulkhead mounting housing when fitted onto a cabinet panel. (See page G.45)	C7I 24	C7I 24 S		
	Surface mounting housings, 2 levers and gasket	M7P 24 25 M7P 24 L225 C7P 24 C7P 24.2		M25 M25 x 2 Pg 21 Pg 21 x 2	
	Surface mounting housings, 2 levers and gasket, high construction, with or without metal cover	M7AP 24.32 M7AP 24.232 M7AP 24.40 M7AP 24.240 C7AP 24.21 C7AP 24.221 C7AP 24.29 C7AP 24.229	M7AP 24 S32 M7AP 24 S232	M32 M32 x 2 M40 M40 x 2 Pg 21 Pg 21 x 2 Pg 29 Pg 29 x 2	

V-TYPE – IP67

E

Inserts size 104.27	Poles	Pages	Inserts size 104.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	24 + ⊕	B.41	CSS 16 A	24 + ⊕	B.121	MIXO modules	C.12-93
CCE 16 A	24 + ⊕	B.47	CT / CTSE* 16 A	24 + ⊕	B.129,133	CX 06 T (6-slot sized MIXO frames)	C.95
CSH / JSH S 16 A	24 + ⊕	B.55,61	CT / CTS* 10 A	64 + ⊕	B.139,141		
CSHT 16 A	24 + ⊕	B.68	CMCE / CMSH 16 A	10 + 2 (aux.) + ⊕	B.146,151		
CQE / CQEY 16 A	46 + ⊕	B.75,85	CX 100 A/16 A	8/0 and 6/6 + ⊕	B.156-157		
CQEE 16 A	64 + ⊕	B.79	CX / CXC 80 A/16 A	4/8 + ⊕	B.161-162		
CD 10 A	64 + ⊕	B.91	*can be used only in bulkhead mounting housings				
CDD 10 A	108 + ⊕	B.97					
CDSH 10 A	42 + ⊕	B.105					

Complete with:


Hoods
Page E.73,77

BIG Hoods
Page E.271

Covers
Page E.76