

BIG series – Multiple cable entries

Hoods with 2 pegs

size **44.27**
**Heavy-Duty
Applications**


EN 60529	IP65 / IP66 / IP69
When coupled with V-TYPE series - IP67 version	IP65 / IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Hoods with 2 pegs, side and/or top entry, without gasket To be used only with a complete cable gland	Side entry	Top entry	
		MBO 06 L40	MBV 06 L40	
		MBO 06 L50	MBV 06 L50	
		Side and Top entries		
		MBVO 06 L240	M40 M50 M40 × 2	
	Hoods with 2 pegs, designed to be drilled, without gasket	Without entry		
		CBC 06 L		
	Hoods with 2 pegs, 2 x top entries, without gasket To be used only with a complete cable gland	MBV 06 L225	M25 × 2	
				MBV 06 L225
	Hoods with 2 pegs, 3 x top entries, without gasket To be used only with a complete cable gland	MBV 06 L320	M20 × 3	
				MBV 06 L320

Inserts size 44.27	Poles	Pages
CNE	16 A 6 + ⊕	B.38
CCE	16 A 6 + ⊕	B.44
CSH / JSH S	16 A 6 + ⊕	B.52,58
CQE / CQEY	16 A 10 + ⊕	B.72,82
CDD	10 A 24 + ⊕	B.94
CDSH / CDSH NC	10 A 9 and 6 + ⊕	B.102,108
CSS	16 A 6 + ⊕	B.118

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 02 T (2-slot sized MIXO frames)	C.95

Complete with:


**V-TYPE
Housings**
Page E.124