

BIG series – Multiple cable entries

Hoods with 4 pegs

size **77.27**
**Heavy-Duty
Applications**


EN 60529	IP65 / IP66 / IP69
When coupled with V-TYPE series - IP67 version	IP65 / IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Hoods with 4 pegs, side and/or top entry, without gasket To be used only with a complete cable gland	Side entry	Top entry	
		MBO 16.40	MBV 16.40	
		MBO 16.50	MBV 16.50	
		Side and Top entries		
		MBVO 16.240	M40 M50 M40 × 2	
	Hoods with 4 pegs, designed to be drilled, without gasket	Without entry		
	Hoods with 4 pegs, 2 x top or side entries, without gasket To be used only with a complete cable gland	Side entry	Top entry	
		MBO 16.225	MBV 16.232	
			M25 × 2 M32 × 2	
	Hoods with 4 pegs, multiple top entries, without gasket To be used only with a complete cable gland			
		MBV 16.325	MBV 16.620	
			M25 × 3 M20 × 6	

Inserts size 77.27	Poles	Pages	Inserts size 77.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE	16 A	16 + ☉ B.40	CP / CPY	35 A	6 + ☉ B.112,114	MIXO modules	C.12-93
CCE	16 A	16 + ☉ B.46	CSS	16 A	16 + ☉ B.120	CX 04 T (4-slot sized MIXO frames)	C.95
CSH / JSH S	16 A	16 + ☉ B.54,60	CMCE / CMSH	16 A	6 + 2 (aux.) + ☉ B.145,150		
CSHT	16 A	16 + ☉ B.67	CX / CXC	80 A/16 A	4/0, 4/2 + ☉ B.158-160		
CQE / CQEY	16 A	32 + ☉ B.74,84					
CQEE	16 A	40 + ☉ B.78	CX	40 A/10 A	6/12, 6/36, 9/42 and 12/2 + ☉ B.163-164, 168-169		
CD	10 A	40 + ☉ B.90					
CDD	10 A	72 + ☉ B.94					
CDSH	10 A	27 + ☉ B.104					

Complete with:


**V-TYPE
Housings**
Page E.126