

# E-Xtreme® – V-TYPE lever version

size **44.27**

Hoods – 2 pegs – without gasket

**3 000 hrs resistance**  
in salt-spray tests

**Aggressive**  
**Environments**





|                                   |                     |
|-----------------------------------|---------------------|
| EN 60529                          | IP66 / IP67 / IP69  |
| UL 50 / UL 50E                    | Type 12 / 4 / 4X    |
| Ambient temperature limits        | -40 °C ... +125 °C* |
| with silicone gasket (on request) | -60 °C ... +125 °C* |
| Mechanical life (cycles)          | ≥ 500               |

\*(&gt;125 °C up to 180 °C with RY inserts)

CE UK



ECBT2.E115072 | ECBT8.E115072

| Item                                                                               | Description                                                                                        | Side entry                                                   | Top entry                                                    | Entry      | Dimension                                                                             |
|------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|--------------------------------------------------------------|--------------------------------------------------------------|------------|---------------------------------------------------------------------------------------|
|   | Hoods, 2 pegs, side entry                                                                          | <a href="#">MHOE 06 L20M</a><br><a href="#">MHOE 06 L25M</a> |                                                              | M20<br>M25 |    |
|   | Hoods, 2 pegs, top entry<br>To be used only with a complete cable gland                            |                                                              | <a href="#">MHVE 06 L20M</a><br><a href="#">MHVE 06 L25M</a> | M20<br>M25 |   |
|  | Hoods, 2 pegs, side or top entry, high construction<br>To be used only with a complete cable gland | <a href="#">MFOE 06 L32M</a><br><a href="#">MFOE 06 L40M</a> | <a href="#">MFVE 06 L32M</a><br><a href="#">MFVE 06 L40M</a> | M32<br>M40 |  |

E-Xtreme®

E

| Inserts size 44.27 | Poles       | Pages     | MIXO Modular Inserts               | Pages   |
|--------------------|-------------|-----------|------------------------------------|---------|
| CNE 16 A           | 6 + ⊕       | B.38      | MIXO modules                       | C.12-93 |
| CCE 16 A           | 6 + ⊕       | B.44      | CX 02 T (2-slot sized MIXO frames) | C.95    |
| CSH / JSH S        | 6 + ⊕       | B.52,58   |                                    |         |
| CQE / CQEY         | 10 + ⊕      | B.72,82   |                                    |         |
| CDD 10 A           | 24 + ⊕      | B.94      |                                    |         |
| CDSH / CDSH NC     | 9 and 6 + ⊕ | B.102,108 |                                    |         |
| CSS 16 A           | 6 + ⊕       | B.118     |                                    |         |

| 180 °C Inserts size 44.27 | Poles      | Pages |
|---------------------------|------------|-------|
| CNE RY**                  | 16 A 6 + ⊕ | I.5   |

\*\* &gt;125 °C up to 180 °C