

Metallic – CKA / MKA

Housings – 1 lever – with rear cable entry

size **21.21**Heavy-Duty
Applications

EN 60529	IP44
With CKR 65	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65	Type 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, 1 stainless steel lever, M20 rear cable entry	MKAX IVG20	M20	
	Bulkhead mounting housings, 1 stainless steel rigid lever, M20 rear cable entry CQC, DNV, BV and cURus pending	MKAXX IVG20	M20	
	Bulkhead mounting housings, 1 galvanized rigid lever, M20 rear cable entry CQC, DNV, BV and cURus pending	MKA IVG20	M20	

Compact 21.21 Inserts	Poles	Pages
CQ4 / CQ / CQY	40 A to 6,5 A	A.4-12
CK / JK / CKSH	10 A	A.16-19
CD / CDY	10 A	A.24-25
CJ (RJ45)	1 A to 2,1 A	A.30-33
CUK (USB)	–	A.36
CLK (Fibre optics)	–	A.38

Note: to obtain the IP66 / IP67 / IP69 degree of protection it is necessary to replace the fixing screw supplied with all inserts, with the one with gasket included in the CKR 65 kit, to be purchased separately, except for the inserts listed below (already supplied with a fixing screw with gasket):

- CQF/M 07, CQF/M 12
- CJ KF
- CJK 8FT / 8IFT
- CUK 2FT / 3FT
- CLK 04 SCF / SCF-H / SCM

Accessories:



CKR 65
gasket and screw kits for
IP66 / IP67 / IP69
Page A.67