

IL-BRID series

Housings and covers – 1 lever – with gasket

size **57.27**Heavy-Duty
Applications

CE UK

EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



(pending CQC)



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	With cover	Entry	Dimension
	Bulkhead mounting housings, 1 lever and gasket, with or without metal cover	CLI 10 L	CLI 10 LS		
	Surface mounting housings, 1 lever and gasket, with or without metal cover	MLP 10 L20 MLP 10 L220	MLP 10 LS20 MLP 10 LS220	M20 M20 × 2	
	Surface mounting housings, 1 lever and gasket, with or without metal cover high construction	MLAP 10 L32 MLAP 10 L232 MLAP 10 L40 MLAP 10 L240	MLAP 10 LS32 MLAP 10 LS232 MLAP 10 LS40 MLAP 10 LS240	M32 M32 × 2 M40 M40 × 2	
	Covers, 1 lever and gasket	CLC 10 LG			
	For enclosures with 2 pegs without gasket with loop for hoods				

Inserts size 57.27	Poles	Pages	Inserts size 57.27	Poles	Pages
CNE	16 A	10 + ☉ B.39	CT / CTSE*	16 A	10 + ☉ B.127,131
CCE	16 A	10 + ☉ B.45	CMCE / CMSH	16 A	3 + 2 (aux.) + ☉ B.144,149
CSH / JSH S	16 A	10 + ☉ B.53,59	CX	40 A/10 A	8/24 + ☉ B.170-171
CSHT	16 A	10 + ☉ B.66	*can be used only in bulkhead mounting housings		
CQE / CQEY	16 A	18 + ☉ B.73,83			
CDD	10 A	42 + ☉ B.95			
CDSH	10 A	18 + ☉ B.103			
CSS	16 A	10 + ☉ B.119			
			MIXO Modular Inserts		Pages
			MIXO modules		C.12-93
			CX 03 T (3-slot sized MIXO frames)		C.95

Complete with:

Hoods
Page E.55Covers
Page E.60