

IL-BRID series

Housings and covers – 1 lever – with gasket

size **77.27**Heavy-Duty
Applications

CE UK

EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

(pending CQC)

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	With cover	Entry	Dimension
	Bulkhead mounting housings, 1 lever and gasket, with or without metal cover	CLI 16 L	CLI 16 LS		
	Surface mounting housings, 1 lever and gasket, with or without metal cover	MLP 16 L25 MLP 16 L225	MLP 16 LS25 MLP 16 LS225	M25 M25 × 2	
	Surface mounting housings, 1 lever and gasket, with or without metal cover high construction	MLAP 16 L32 MLAP 16 L232 MLAP 16 L40 MLAP 16 L240	MLAP 16 LS32 MLAP 16 LS232 MLAP 16 LS40 MLAP 16 LS240	M32 M32 × 2 M40 M40 × 2	
	Covers, 1 lever and gasket	CLC 16 LG			
	For enclosures with 2 pegs without gasket with loop for hoods				

Inserts size 77.27	Poles	Pages	Inserts size 77.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	16 + ⊕	B.40	CP / CPY 35 A	6 + ⊕	B.112,114	MIXO modules	C.12-93
CCE 16 A	16 + ⊕	B.46	CSS 16 A	16 + ⊕	B.120	CX 04 T (4-slot sized MIXO frames)	C.95
CSH / JSH S 16 A	16 + ⊕	B.54,60	CT / CTSE* 16 A	16 + ⊕	B.128,132		
CSHT 16 A	16 + ⊕	B.67	CT / CTS* 10 A	40 + ⊕	B.138,140		
CQE / CQEY 16 A	32 + ⊕	B.74,84	CMCE / CMSH 16 A	6 + 2 (aux.) + ⊕	B.145,150		
CQEE 16 A	40 + ⊕	B.78	CX / CXC 80 A/16 A	4/0, 4/2 + ⊕	B.158-160		
CD 10 A	40 + ⊕	B.90	CX 40 A/10 A	6/12, 6/36, 9/42 and 12/2 + ⊕	B.163-164, 168-169		
CDD 10 A	72 + ⊕	B.94					
CDSH 10 A	27 + ⊕	B.104					

*can be used only in bulkhead mounting housings

Complete with:

Hoods
Page E.63Covers
Page E.68