

# IL-BRID series

## Hoods – 1 lever – with gasket

size **44.27**
**Heavy-Duty  
Applications**

**CE UK**




|                            |                    |
|----------------------------|--------------------|
| EN 60529                   | IP65 / IP66 / IP69 |
| UL 50 / UL 50E             | Type 12 / 4 / 4X   |
| Ambient temperature limits | -40 °C ... +125 °C |
| Mechanical life (cycles)   | ≥ 500              |



(pending CQC)



ECBT2.E115072 | ECBT8.E115072

| Item                                                                                | Description                                                                                                        | Side entry                   | Top entry                                                                                    | Entry             | Dimension                                                                             |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|------------------------------|----------------------------------------------------------------------------------------------|-------------------|---------------------------------------------------------------------------------------|
|    | Hoods, 1 lever and gasket, top entry                                                                               |                              | <a href="#">MLV 06 LG25</a>                                                                  | M25               |    |
|    | Hoods, 1 lever and gasket, top entry, high construction, with metal adapter                                        |                              | <a href="#">MLAV 06 LG25</a><br><a href="#">MLAV 06 LG32</a>                                 | M25<br>M32        |   |
|  | Hoods, 1 lever and gasket, side or top entry, high construction<br><br>To be used only with a complete cable gland | <a href="#">MLFO 06 LG40</a> | <a href="#">MLFV 06 LG25</a><br><a href="#">MLFV 06 LG32</a><br><a href="#">MLFV 06 LG40</a> | M25<br>M32<br>M40 |  |

IL-BRID

E

| Inserts size 44.27 | Poles            | Pages     |
|--------------------|------------------|-----------|
| CNE                | 16 A 6 + ⊕       | B.38      |
| CCE                | 16 A 6 + ⊕       | B.44      |
| CSH / JSH S        | 16 A 6 + ⊕       | B.52,58   |
| CQE / CQEY         | 16 A 10 + ⊕      | B.72,82   |
| CDD                | 10 A 24 + ⊕      | B.94      |
| CDSH / CDSH NC     | 10 A 9 and 6 + ⊕ | B.102,108 |
| CSS                | 16 A 6 + ⊕       | B.118     |

| MIXO Modular Inserts               | Pages   |
|------------------------------------|---------|
| MIXO modules                       | C.12-93 |
| CX 02 T (2-slot sized MIXO frames) | C.95    |

Complete with:


**Hoods**  
Page E.49

**Covers**  
Page E.52