

Slim enclosures with IL-BRID lever

Housings, hoods and covers – 1 lever

size **49.16**
**Heavy-Duty
Applications**


CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	With cover	Entry	Dimension
	Bulkhead mounting housings, 1 lever, without gasket, with or without metal cover or SIMPLEX self-closing plastic cover	CZI 15 L	CZI 15 LS SIMPLEX cover CZI 15 LSP		
	Surface mounting housings, 1 lever, without gasket, with or without metal cover	MZP 15 L25 MZP 15 L225 CZP 15 L CZP 15 L2 CZP 15 L21 CZP 15 L221	MZP 15 LS25 MZP 15 LS225 CZP 15 LS CZP 15 LS2 CZP 15 LS21 CZP 15 LS221	M25 M25 × 2 Pg 16 Pg 16 × 2 Pg 21 Pg 21 × 2	
	Surface mounting housings, 1 lever, without gasket, with SIMPLEX self-closing plastic cover	MZP 15 LSP20 MZP 15 LSP25 CZP 15 LSP16 CZP 15 LSP21		M20 M25 Pg 16 Pg 21	
	Hoods, 1 lever, without gasket, top entry	MZV 15 LG20 CZV 15 LG		M20 Pg 13,5	
	Covers, 1 lever, without gasket	CZC 15 LG			
	- with loop				

Inserts size 49.16	Poles	Pages
CDA 16 A	10 + ⊕	B.16
CDC 16 A	10 + ⊕	B.19
CSAH 16 A	10 + ⊕	B.24
CD 10 A	15 + ⊕	B.30

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 01 T (1-slot sized MIXO frames)	C.94

Notes:

The enclosures ensure IP66/IP69 degree of protection (or IP65 for hinged cover versions) when mated and locked with the closing levers.

Enclosures with SIMPLEX self-closing cover ensure IP44 degree of protection when not mated and locked with lever.