

Slim enclosures with IL-BRID lever

size **49.16**

Hoods and covers – 2 pegs

Heavy-Duty
Applications







CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 pegs, with gasket, side entry	MZO 15 L20 MZO 15 L25 CZO 15 L		M20 M25 Pg 16	
	Hoods, 2 pegs, with gasket, top entry		MZV 15 L20 CZV 15 L	M20 Pg 13,5	
 	Hoods, 2 pegs, with gasket, side or top entry, high construction To be used only with a complete cable gland	MZFO 15 L20 MZFO 15 L25 CZFO 15 L16 CZFO 15 L21	MZFV 15 L20 MZFV 15 L25 CZFV 15 L16 CZFV 15 L21	M20 M25 Pg 16 Pg 21	
	Hoods, 2 pegs, with gasket, high construction, designed to be drilled	Without entry CZAC 15 L			
	Covers, 2 pegs, with gasket - with loop  - or eyelet 	With loop CZC 15 SL	With eyelet CZC 15 L		

Inserts size 49.16		Poles	Pages
CDA	16 A	10 + ⊕	B.16
CDC	16 A	10 + ⊕	B.19
CSAH	16 A	10 + ⊕	B.24
CD	10 A	15 + ⊕	B.30

MIXO Modular Inserts		Pages
MIXO modules		C.12-93
CX 01 T (1-slot sized MIXO frames)		C.94