

HNM series – High Number of Mating cycles

size **77.27**





Hoods – 2 anti-friction pegs – without gasket

**Specialized
Applications**

CE UK
**DNV BUREAU
VERITAS**

EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 10 000

ALUS ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 pegs, without gasket, side entry	RHO 16 L32		M32	
	Hoods, 2 pegs, without gasket, top entry		RHV 16 L32	M32	
	Hoods, 2 pegs, without gasket, side or top entry, high construction	RFO 16 L32	RFV 16 L32	M32	
	Hoods, 2 pegs, without gasket, high construction, designed to be drilled	Without entry			

Inserts size 77.27	Poles	Pages	MIXO Modular Inserts	Pages
RCE 16 A	16 + ⊕	H.12	MIXO HNM modules	H.38-60
RSH 16 A	16 + ⊕	H.16	RX 04 T (4-slot sized MIXO HNM frames)	H.62
RQEE 16 A	40 + ⊕	H.18		
RD 10 A	40 + ⊕	H.20		
RDD 10 A	72 + ⊕	H.24		
RDSH 10 A	27 + ⊕	H.28		
RXC 80 A / 16 A	4/2 + ⊕	H.30		
RX 40 A / 10 A	12/2 + ⊕	H.32		

Accessories:

CR 16 DF
Self-centring floating
frame HNM
Page H.64