



Contact resistance	≤ 10 mΩ
Mechanical life (cycles)	≥ 500

(pending: cURus)

Item	Description	Part No.	Part No.	Dimension
	10 A crimp contacts (loose parts) 1 packaging unit: 200 pcs. section (mm ²) section (AWG) 0,37-1 24-18 1,5-2,5 16-14	Male silver SDMA 1.0 SDMA 2.5	Female SDFA 1.0 SDFA 2.5	
	10 A crimp contacts (reel package) 1 packaging unit: 5.000 pcs. section (mm ²) section (AWG) 0,37-1 24-18 1,5-2,5 16-14	silver SDMA 1.0R SDMA 2.5R	SDFA 1.0R SDFA 2.5R	
				
	Loose parts recommended crimping tool: SIPZ W Reel package recommended crimping tool: suitable for stripping / crimping automated machines to be used with 5 000 pieces reels, see pages F.52 for 10 A crimp contacts.			

Materials
 Contacts copper alloy, silver ● plated

Inserts		Pages
CQ4 03/2*	40 A/ 10 A	A.7
CQ 07 / CQ 12	10 A	A.10-11
CD 07 / CD 08	10 A	A.22, 24
CX 1/2 BD*	10 A	A.37
CQ 04/2E*	40 A/ 10 A	B.6
CQ 04/2* / CQ 04/2B*	40 A/ 10 A	B.7-8
CQ 17	10 A	B.12
CD	10 A	B.30-32
CDD	10 A	B.33-34
CD	10 A	B.90-93
CDD	10 A	B.94-99
CX 12/2*	40 A/ 10 A	B.163
CX 6/12*	40 A/ 10 A	B.164
CX 9/42*	40 A/ 10 A	B.168
CX 6/36*	40 A/ 10 A	B.169
CX 8/24*	16 A/ 10 A	B.170-171
MIXO modules	10 A	C.46,48-49,58,64,74-75

* The insert polarities that require the contacts shown on this page as auxiliaries are highlighted in **bold**.