

T-TYPE Hygienic series – Food and Beverage

size **57.27**

T-TYPE/H Housings and hoods for production lines

T-TYPE/C Housings and hoods for low-temperatures

Specialized
Applications

EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 – Type 4 / 4X Indoor Use Only
Ambient temperature limits	T-TYPE/H: -40 °C ... +70 °C T-TYPE/C: -50 °C ... +70 °C
Mechanical life (cycles)	≥ 500

CE UK



(pending: CQC)



ECBT2.E115072 | ECBT8.E115072

Item	Description	T-TYPE/H	T-TYPE/C	Entry	Dimension
	Bulkhead mounting housings, 2 levers	THIH 10	THIC 10		
	- HNBR gasket for T-TYPE/H - SILICONE gasket for T-TYPE/C				
	Surface mounting housings, 2 levers, high construction	TAPH 10.25 TAPH 10.32	TAPC 10.25 TAPC 10.32	M25 M32	
	- HNBR gasket for T-TYPE/H - SILICONE gasket for T-TYPE/C Supplied with an open threaded entry and diametrically opposite a closed threaded entry which can be opened by the user if required (with suitable tool).				
	Hoods, 2 levers and gasket, top entry, high construction	TAVH 10 G25 TAVH 10 G32	TAVC 10 G25 TAVC 10 G32	M25 M32	
	- HNBR gasket for T-TYPE/H - SILICONE gasket for T-TYPE/C				

T-TYPE/H and T-TYPE/C

E

Inserts size 57.27	Poles	Pages	Inserts size 57.27	Poles	Pages
CNE	16 A	10 + ☉ B.39	CMCE / CMSH	16 A	3 + 2 (aux.) + ☉ B.144,149
CCE	16 A	10 + ☉ B.45	CX	40 A/10 A	8/24 + ☉ B.170-171
CSH / JSH S	16 A	10 + ☉ B.53,59			
CSHT	16 A	10 + ☉ B.66			
CQE / CQEY	16 A	18 + ☉ B.73,83			
CDD	10 A	42 + ☉ B.95			
CDSH	10 A	18 + ☉ B.103			
CSS	16 A	10 + ☉ B.119			
			MIXO Modular Inserts		Pages
			MIXO modules		C.12-93
			CX 03 T (3-slot sized MIXO frames)		C.95

Complete with:

Hoods
Page E.229Covers
Page E.235PE jumpers
(Optional)
Page E.249