

T-TYPE series – Insulating

size **44.27**

T-TYPE Housings and hoods for Heavy-Duty Applications

T-TYPE/W Housings and hoods for Aggressive Environments

Aggressive
EnvironmentsHeavy-Duty
Applications





EN 60529	T-TYPE: IP65
	T-TYPE/W: IP65 / IP66 / IP69
UL 50 / UL 50E	T-TYPE: Type 12
	T-TYPE/W: Type 12 – Type 4 / 4X Indoor Use Only
Ambient temperature limits	-40 °C ... +90 °C
Mechanical life (cycles)	≥ 500

CE UK

(pending: CQC)

CIRIUS

ECBT2.E115072 | ECBT8.E115072

Item	Description	T-TYPE	T-TYPE/W	Entry	Dimension
	Bulkhead mounting housings, 1 lever and gasket - PUR gasket for T-TYPE - FKM gasket for T-TYPE/W	TCHI 06 L	THIW 06 L		
	Surface mounting housings, 1 lever and gasket, high construction - PUR gasket for T-TYPE - FKM gasket for T-TYPE/W Supplied with an open threaded entry and diametrically opposite a closed threaded entry which can be opened by the user if required (with suitable tool).	TMAP 06 L25 TMAP 06 L32	TAPW 06 L25 TAPW 06 L32	M25 M32	
	Hoods, 1 lever and gasket, top entry, high construction - PUR gasket for T-TYPE - FKM gasket for T-TYPE/W	TMAV 06 LG25 TMAV 06 LG32	TAVW 06 LG25 TAVW 06 LG32	M25 M32	

Inserts size 44.27	Poles	Pages	MIXO Modular Inserts	Pages	
CNE	16 A	6 + ⊕	B.38	MIXO modules	C.12-93
CCE	16 A	6 + ⊕	B.44	CX 02 T (2-slot sized MIXO frames)	C.95
CSH / JSH S	16 A	6 + ⊕	B.52,58		
CQE / CQEY	16 A	10 + ⊕	B.72,82		
CDD	10 A	24 + ⊕	B.94		
CDSH / CDSH NC	10 A	9 and 6 + ⊕	B.102,108		
CSS	16 A	6 + ⊕	B.118		

Accessories:


CR BPE
PE jumpers

Page E.236