

T-TYPE series – Insulating

size **77.27**

T-TYPE Housings and hoods for Heavy-Duty Applications

T-TYPE/W Housings and hoods for Aggressive Environments

Aggressive
EnvironmentsHeavy-Duty
Applications

EN 60529

T-TYPE: IP65

T-TYPE/W: IP65 / IP66 / IP69

UL 50 / UL 50E

T-TYPE: Type 12

T-TYPE/W: Type 12 – Type 4 / 4X Indoor Use Only

Ambient temperature limits

-40 °C ... +90 °C

Mechanical life (cycles)

≥ 500

CE UK

BUREAU
VERITAS

(pending: CQC)



ECBT2.E115072 | ECBT8.E115072

Item	Description	T-TYPE	T-TYPE/W	Entry	Dimension
	Bulkhead mounting housings, 2 levers and gasket	TCHI 16	THIW 16		
	- PUR gasket for T-TYPE - FKM gasket for T-TYPE/W				
	Surface mounting housings, 2 levers and gasket, high construction	TMAP 16.32 TMAP 16.40	TAPW 16.32 TAPW 16.40	M32 M40	
	- PUR gasket for T-TYPE - FKM gasket for T-TYPE/W Supplied with an open threaded entry and diametrically opposite a closed threaded entry which can be opened by the user if required (with suitable tool).				
	Hoods, 2 levers and gasket, top entry, high construction	TMAV 16 G32 TMAV 16 G40	TAVW 16 G32 TAVW 16 G40	M32 M40	
	- PUR gasket for T-TYPE - FKM gasket for T-TYPE/W				

Inserts size 77.27	Poles	Pages	Inserts size 77.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	16 + ⊕	B.40	CP / CPY 35 A	6 + ⊕	B.112,114	MIXO modules	C.12-93
CCE 16 A	16 + ⊕	B.46	CSS 16 A	16 + ⊕	B.120	CX 04 T (4-slot sized MIXO frames)	C.95
CSH / JSH S 16 A	16 + ⊕	B.54,60	CMCE / CMSH 16 A	6 + 2 (aux.) + ⊕	B.145,150		
CSHT 16 A	16 + ⊕	B.67	CX / CXC 80 A/16 A	4/0, 4/2 + ⊕	B.158-160		
CQE / CQEY 16 A	32 + ⊕	B.74,84	CX 40 A/10 A	6/12, 6/36, 9/42 and 12/2 + ⊕	B.163-164, 168-169	Accessories: CR BPE PE jumpers Page E.236	
CQEE 16 A	40 + ⊕	B.78					
CD 10 A	40 + ⊕	B.90					
CDD 10 A	72 + ⊕	B.94					
CDSH 10 A	27 + ⊕	B.104					