

# ST

## Plugs for cable grommets



Plugs are used to close either KT or QT grommets which are not equipped with cables. IP ratings of the grommets remain.

Perfect for applications where cables have been removed or might be routed at a later stage.

### Advantages & benefits

- Sealing unused cable grommets

### Specifications

|                |                               |
|----------------|-------------------------------|
| Material       | Polyamide (PA), white         |
| Flame class    | UL 94 V-0, self-extinguishing |
| IP rating      | IP rating of grommets remains |
| UL type rating | UL type 12 (acc. to UL 50E)   |
| Temperature    | -40°C to +120°C               |
| Properties     | Halogen-free, silicone-free   |

### Compatible with

|                   |           |
|-------------------|-----------|
| KT Cable grommets | 74 - 89   |
| QT Cable grommets | 118 - 119 |

| Type   | Order No. | Diameter D | Length L | PU |
|--------|-----------|------------|----------|----|
| ST 1   | 42900     | 1 mm       | 25 mm    | 25 |
| ST 2   | 42909     | 2 mm       | 25 mm    | 25 |
| ST 3   | 42901     | 3 mm       | 25 mm    | 25 |
| ST 4   | 42908     | 4 mm       | 25 mm    | 25 |
| ST 5   | 42906     | 5 mm       | 25 mm    | 25 |
| ST 6   | 42903     | 6 mm       | 25 mm    | 25 |
| ST 7   | 42905     | 7 mm       | 25 mm    | 25 |
| ST 8   | 42899     | 8 mm       | 20 mm    | 25 |
| ST 9   | 42897     | 9 mm       | 20 mm    | 25 |
| ST 10  | 42895     | 10 mm      | 20 mm    | 25 |
| ST 11  | 42893     | 11 mm      | 20 mm    | 25 |
| ST 12  | 42891     | 12 mm      | 20 mm    | 25 |
| ST 13  | 42889     | 13 mm      | 20 mm    | 25 |
| ST 14  | 42887     | 14 mm      | 20 mm    | 25 |
| ST 15  | 42885     | 15 mm      | 20 mm    | 25 |
| ST 16  | 42883     | 16 mm      | 20 mm    | 25 |
| ST 17  | 42881     | 17 mm      | 20 mm    | 25 |
| ST ASI | 42877     | –          | 25 mm    | 25 |

