



Enclosure series C-TYPE

From catalogue
page 386 of
CN.19



Creating Connectors



Description

The standard connector housings for every type of contact insert with many ILME-specific features. The greatest selection of sizes and housing types, the unique locking lever with roller and double spring made of stainless steel, the easy-to-assemble gasket with internal and external profile collar and much more characterize this series.

Technical data

- Housing made of die-cast aluminum with locking levers made of stainless steel
- Size 44.27 to 104.62
- Protection degree IP65 / IP66 / IP69
- Temperature range - 40°C bis + 125°C
- 2- or 4-fold lock with tolerance compensation
- Profile collar gasket made of durable NBR material
- Epoxy-based powder coating (IK impact-resistant)
- Laser marking with important characteristics
- All threads free of powder coating
- Interchangeable handles made of thermoplastic
- Standard mounting dimensions compatible with the market standard

Article codes



CHI... (Bulkhead mounting h.)	MHO...
MHP... (Surface mounting h.)	(Hood, side cable entry)
MHV...G (Hood with levers)	MHV...
	(Hood, straight cable entry)
CHC... (Cover)	MIO...
CAC... (Hood without entry)	(Hood, enlarged)

Advantages

- Always the right housing thanks to the largest selection of sizes and housing types
- Backwards compatible due to maximum compatibility with the market standard
- Durable and reliable with many of ILME's own features (lock, gasket, and so on)



Enclosure series C-TYPE



Creating Connectors

