

KEL-QUICK

Cable entry frames
for quick assembly



IP54



Cover lid is simply snapped onto the frame.



Tool-free mounting with KEL-SNAP frame.



Slit QT grommets

Product description

The KEL-QUICK range is a compact system to route and seal pre-terminated cables as well as conduits or pneumatic hoses utilising split QT grommets. After populating the entry frame with QT grommets and cables, the cover lid is snapped onto the frame without using tools. The KEL-QUICK frames match exactly the cut-out dimensions for 24-, 16- and 10-pin standard industrial connectors. The KEL-QUICK-B matches cut-out dimensions of 36×46 mm. KEL-QUICK frames can either be screw mounted or simply snapped into the KEL-SNAP frame. A flat rubber gasket is included in the shipment.

Advantages & benefits

- Fast and easy assembly and when used with the KEL-SNAP frame, mounting without tools possible
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of the cable grommets
Temperature	- 40°C to + 140°C (static)
Properties	Halogen-free, silicone-free
Drilling template	See Page 218 - 219
Frame depth	17 mm

Accessories

QT Cable grommets	66
KEL-SNAP Mounting frames	31
KEL-EMC Cable collectors	138 - 140
KDR Base plates	164 - 177
FP Flange plates	178 - 183
MP Module plates	174 - 175
ST Plugs	53

Description	Type	Order No.	Cut-out [mm]	Grommets	PU
	KEL-QUICK 24 10	42410	36 × 112	10 QT	10
	KEL-QUICK 16 8	42418	36 × 86	8 QT	10
	KEL-QUICK 10 6	42420	36 × 65	6 QT	10
	KEL-QUICK-B4	42434	36 × 46	4 QT	10