

Thermoplastic – CK / MK

Hoods and covers – 1 lever

size **21.21**Heavy-Duty
Applications

EN 60529	IP44
With CKR 65	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65	Type 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK

(pending: CQC, DNV and BV)

(pending: cURus)

Item	Description	Light grey	Jet black	Entry	Dimension
	Hoods, 1 lever, top entry	MK VG20	MK VGN20	M20	
	Not suitable for CQ4 series inserts	CK 03 VGS	CK 03 VGNS	Pg 11	
	Hoods, 1 lever, top entry	MK VG25	MK VGN25	M25	
	Covers, 1 lever, with or without gasket	With gasket (for female inserts)			
	For hoods with 2 pegs with loop	CK 03 CX	CK 03 CXN		
		Without gasket (for male inserts)			
		CK 03 CXA	CK 03 CXAN		

Compact 21.21 Inserts	Poles	Pages
CQ4 / CQ / CQY	40 A to 6,5 A	A.4-12
CK / JK / CKSH	10 A	A.16-19
CD / CDY	10 A	A.22-23
CD / CDY	10 A	A.24-25
CJ (RJ45)	1 A to 2,1 A	A.30-33
CUK (USB)	–	A.36
CX (BUS)	10 A	A.37
CLK (Fibre optics)	–	A.38

Note: to obtain the IP66 / IP67 / IP69 degree of protection it is necessary to replace the fixing screw supplied with all inserts, with the one with gasket included in the CKR 65 kit, to be purchased separately, except for the inserts listed below (already supplied with a fixing screw with gasket):

- CQF/M 07, CQF/M 12
- CJ KF
- CJK 8FT / 8IFT
- CUK 2FT / 3FT
- CX 1/2 BDF/M
- CLK 04 SCF / SCF-H / SCM

Accessories:



CKR 65
gasket and screw kits for
IP66 / IP67 / IP69
Page A.67