






CLPZ R

Data connectors tools

for POF / MOST® crimp contacts

Item	Description	Part No.
	Manual crimping tool for POF CX PL and MOST® CX ML contacts, RENNSTEIG model On request tool CLPZ RATIOPLAST 910 CZ 001 00 008 for POF and MOST® contacts crimping on the back	CLPZ R
	Polishing disc (RATIOPLAST 910 PS 0SC 00 001) for POF and MOST® contacts	CLDL
	Polish paper: grain size 1000 (RATIOPLAST 910 PB 001 00 001) grain size 4000 (RATIOPLAST 910 PB 001 40 250)	CLC1 CLC4
	Jacket stripper for POF and MOST® fibre optic with PA jacket (RATIOPLAST 910 AZ 001 00 PA1) Fibre stripper for POF fibre optic (RATIOPLAST 910 AB 001 00 001)	CLSG CLSP
	Cable cutter for Ø 2,3 mm max for POF and MOST® fibre optic (RATIOPLAST 910 SW 001 00 001)	CLTE

As alternative to crimping please use glue UHU PLUS ENDFEST 300 (BICOMPONENT),

part No. "CL GL" (provide a strain relief by cable glands):

- mix the two components on a sheet (just a drop/each)
- the stripped ca. 5 mm POF (that means the inner fibre) has to be dipped in the glue (just 5 mm);
- the POF has to be pushed now in the contact/ferrule;
- min. one night to hard/dry the glue;
- finally the POF has to be polished (polishing disc).

Contacts	Pages
CX PLM / PLF	C.81
CX MLM / MLF	C.81