













KEL-ULTRA flex

Cable entry grommets



Туре	Order No.	Sealing range	PU
KEL-ULTRA flex 1 incl. fixing screws	42630	25 - max. 90 mm cable diameter	1
KEL-ULTRA flex 2 incl. fixing screws	42631	75 - max. 115 mm cable diameter	1



Product description

The KEL-ULTRA flex is designed as a cable entry grommet for any large cable or conduit that is difficult to manage. The KEL-ULTRA flex comes in two sizes and is ideal for routing and sealing cables and conduits with a diameter from 25 to 115 mm. Due to the high flexibility of the elastomer pyramid, inserting large, thick cables with KEL-ULTRA flex is easier than using standard cable glands.

After inserting the cable or conduit, the KEL-ULTRA flex is quickly and easily mounted with the metal ring and screws. This ring enables a circular fixing and sealing of the grommet at the enclosure wall. The ring is supplied with each KEL-ULTRA flex. Cutting of grommets: Cable diameter less 25%. It is recommended that additional strain relief be provided for cables as part of the installation.

Advantages & benefits

Quick assembly

Material

- Grommets allow easy orientation and seal of rigid cables
- IP66 / up to UL type 12 rating

Specifications

Fixing metal ring: Steel, zinc-plated
Blind plate: Steel, zinc-plated
UL94-Vo, self-extinguishing
IP rating
IP66, when fastened with 8 screws
(certified acc. to EN 60529)
UL type rating
Temperature
Properties

Fixing metal ring: Steel, zinc-plated
UL94-Vo, self-extinguishing
IP66, when fastened with 8 screws
(certified acc. to EN 60529)
UL type 12 (acc. to UL 50E)
- 40°C to + 90°C (static)
Halogen-free, silicone-free

Pyramid: Elastomer

max. ø 140 mm

Round, ø-cable +30%,

Accessories

Cut-out dimension

MP Module plates 174 - 175 BPM Blank plates 185