

# E-Xtreme® – V-TYPE lever version

size **57.27**

Hoods – 4 pegs – without gasket

**3 000 hrs resistance**  
in salt-spray tests

**Aggressive**  
**Environments**





|                                   |                     |
|-----------------------------------|---------------------|
| EN 60529                          | IP66 / IP67 / IP69  |
| UL 50 / UL 50E                    | Type 12 / 4 / 4X    |
| Ambient temperature limits        | -40 °C ... +125 °C* |
| with silicone gasket (on request) | -60 °C ... +125 °C* |
| Mechanical life (cycles)          | ≥ 500               |

\*(&gt;125 °C up to 180 °C with RY inserts)

CE UK



ECBT2.E115072 | ECBT8.E115072

| Item                                                                               | Description                                                                                        | Side entry                                                 | Top entry                                                  | Entry      | Dimension                                                                             |
|------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|------------------------------------------------------------|------------------------------------------------------------|------------|---------------------------------------------------------------------------------------|
|   | Hoods, 4 pegs, side entry                                                                          | <a href="#">MHOE 10.20M</a><br><a href="#">MHOE 10.25M</a> |                                                            | M20<br>M25 |    |
|   | Hoods, 4 pegs, top entry<br>To be used only with a complete cable gland                            |                                                            | <a href="#">MHVE 10.20M</a><br><a href="#">MHVE 10.25M</a> | M20<br>M25 |    |
|  | Hoods, 4 pegs, side or top entry, high construction<br>To be used only with a complete cable gland | <a href="#">MFOE 10.32M</a><br><a href="#">MFOE 10.40M</a> | <a href="#">MFVE 10.32M</a><br><a href="#">MFVE 10.40M</a> | M32<br>M40 |  |

E-Xtreme®

E

| Inserts size 57.27 |      |        |         | Inserts size 57.27                 |           |                  |           | 180 °C Inserts size 57.27 |      |        |       |
|--------------------|------|--------|---------|------------------------------------|-----------|------------------|-----------|---------------------------|------|--------|-------|
|                    |      | Poles  | Pages   |                                    |           | Poles            | Pages     |                           |      | Poles  | Pages |
| CNE                | 16 A | 10 + ☉ | B.39    | CMCE / CMSH                        | 16 A      | 3 + 2 (aux.) + ☉ | B.144,149 | CNE RY**                  | 16 A | 10 + ☉ | I.6   |
| CCE                | 16 A | 10 + ☉ | B.45    | CX                                 | 40 A/10 A | 8/24 + ☉         | B.170-171 | ** >125 °C up to 180 °C   |      |        |       |
| CSH / JSH S        | 16 A | 10 + ☉ | B.53,59 |                                    |           |                  |           |                           |      |        |       |
| CSHT               | 16 A | 10 + ☉ | B.66    |                                    |           |                  |           |                           |      |        |       |
| CQE / CQEY         | 16 A | 18 + ☉ | B.73,83 |                                    |           |                  |           |                           |      |        |       |
| CDD                | 10 A | 42 + ☉ | B.95    |                                    |           |                  |           |                           |      |        |       |
| CDSH               | 10 A | 18 + ☉ | B.103   |                                    |           |                  |           |                           |      |        |       |
| CSS                | 16 A | 10 + ☉ | B.119   |                                    |           |                  |           |                           |      |        |       |
|                    |      |        |         | <b>MIXO Modular Inserts</b>        |           |                  |           |                           |      |        |       |
|                    |      |        |         | MIXO modules                       |           |                  |           | C.12-93                   |      |        |       |
|                    |      |        |         | CX 03 T (3-slot sized MIXO frames) |           |                  |           | C.95                      |      |        |       |