

Slim enclosures – EMC series

size **66.16**

Hoods and covers – 2 pegs

Specialized
Applications






CE UK



EN 60529	IP65 / IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 pegs and gasket, side entry	MZOS 25 L20 MZOS 25 L25 CZOS 25 L		M20 M25 Pg 16	
	Hoods, 2 pegs and gasket, top entry To be used only with a complete cable gland		MZVS 25 L20 CZVS 25 L	M20 Pg 16	
	Hoods, 2 pegs and gasket, side or top entry, high construction To be used only with a complete cable gland	MZFOS 25 L25 CZFOS 25 L21	MZFVS 25 L25 CZFVS 25 L21	M25 Pg 21	
	Cover, 2 pegs and gasket For enclosures with 1 lever without gasket with eyelet for housings 		With eyelet CZCS 25 L		

Inserts size 66.16		Poles	Pages
CDA	16 A	16 + ⊕	B.17
CDC	16 A	16 + ⊕	B.20
CSAH	16 A	16 + ⊕	B.25
CD	10 A	25 + ⊕	B.31
CDD	10 A	38 + ⊕	B.33