

HNM series – High Number of Mating cycles

size **21.21**

Housings and hoods – 1 lever

Specialized
Applications


EN 60529	IP44
With CKR 65 (D)	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65 (D)	Type 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 5 000

CE UK

DNV BUREAU VERITAS

cALUS

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Angled bulkhead mounting housings, 1 stainless steel lever, with cable entry, open or closed bottom flange Not suitable for CQ4 series inserts	Open bottom flange RKAX IAP20	M20	
		Closed bottom flange RKAX AP20	M20	
	Angled surface mounting housings, 1 stainless steel lever, with cable entry, fixing by 4 screws, open or closed bottom flange	Open bottom RKAX IAP25	M25	
		Closed bottom RKAX AP25	M25	
	Hoods, 1 stainless steel lever, top entry Not suitable for CQ4 series inserts	RKAX VG20	M20	
	Hoods, 1 stainless steel lever, top entry	RKAX VG25	M25	

Compact 21.21 Inserts	Poles	Pages
CQ4	40 A	3 + ☺ H.6
RQ	16 A	5 + ☺ H.7
CQ	6,5 A	21 + ☺ H.8
CD	10 A	8 H.9

Note: to obtain the IP66 / IP67 / IP69 degree of protection it is necessary to replace the fixing screw supplied with all inserts, with the one with gasket included in the CKR 65 kit, to be purchased separately, except for the inserts listed below (already supplied with a fixing screw with gasket):

- CQF/M 07, CQF/M 12
- CUK 2FT /3FT
- CJ KF
- CX 1/2 BDF/M
- CJK 8FT /8IFT
- CLK 04 SCF /SCF-H /SCM

Complete with:



Hoods
21.21 enclosures
Pages A.64

Accessories:



CKR 65
gasket and screw kits
for IP66 / IP67 / IP69, page A.67