

T-TYPE series – Insulating

size **57.27**

T-TYPE Housings and hoods for Heavy-Duty Applications

T-TYPE/W Housings and hoods for Aggressive Environments

Aggressive
EnvironmentsHeavy-Duty
Applications

EN 60529

T-TYPE: IP65

T-TYPE/W: IP65 / IP66 / IP69

UL 50 / UL 50E

T-TYPE: Type 12

T-TYPE/W: Type 12 – Type 4 / 4X Indoor Use Only

Ambient temperature limits

-40 °C ... +90 °C

Mechanical life (cycles)

≥ 500

CE UK

BUREAU
VERITAS

(pending: CQC)



ECBT2.E115072 | ECBT8.E115072

Item	Description	T-TYPE	T-TYPE/W	Entry	Dimension
	Bulkhead mounting housings, 2 levers and gasket	TCHI 10	THIW 10		
	- PUR gasket for T-TYPE - FKM gasket for T-TYPE/W				
	Surface mounting housings, 2 levers and gasket, high construction	TMAP 10.25 TMAP 10.32	TAPW 10.25 TAPW 10.32	M25 M32	
	- PUR gasket for T-TYPE - FKM gasket for T-TYPE/W Supplied with an open threaded entry and diametrically opposite a closed threaded entry which can be opened by the user if required (with suitable tool).				
	Hoods, 2 levers and gasket, top entry, high construction	TMAV 10 G25 TMAV 10 G32	TAVW 10 G25 TAVW 10 G32	M25 M32	
	- PUR gasket for T-TYPE - FKM gasket for T-TYPE/W				

Inserts size 57.27	Poles	Pages	Inserts size 57.27	Poles	Pages
CNE	16 A	10 + ☉ B.39	CMCE / CMSH	16 A	3 + 2 (aux.) + ☉ B.144,149
CCE	16 A	10 + ☉ B.45	CX	40 A/10 A	8/24 + ☉ B.170-171
CSH / JSH S	16 A	10 + ☉ B.53,59			
CSHT	16 A	10 + ☉ B.66			
CQE / CQEY	16 A	18 + ☉ B.73,83			
CDD	10 A	42 + ☉ B.95			
CDSH	10 A	18 + ☉ B.103			
CSS	16 A	10 + ☉ B.119			
			MIXO Modular Inserts		Pages
			MIXO modules		C.12-93
			CX 03 T (3-slot sized MIXO frames)		C.95

Accessories:

CR BPE
PE jumpers

Page E.236