

Thermoplastic – CK / MK – DESINA®

size **21.21**

Hoods and covers – 2 pegs







**Heavy-Duty
Applications**


EN 60529	IP44
With CKR 65	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65	Type 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Light grey	Jet black	Entry	Dimension
 	Hoods, 2 pegs and glued gasket, side entry DESINA® version	MKG VA20 CKG 03 VA	MKG VAN20 CKG 03 VAN	M20 Pg 11	
 	Hoods, 2 pegs and glued gasket, top entry DESINA® version	MKG V20 CKG 03 V	MKG VN20 CKG 03 VN	M20 Pg 11	
 	Hoods, 2 pegs and glued gasket, side entry DESINA® version	MKG VA25	MKG VAN25	M25	
 	Hoods, 2 pegs and glued gasket, top entry DESINA® version	MKG V25	MKG VN25	M25	
 	Covers, 2 pegs and glued gasket DESINA® version For housings with 1 lever with eyelet 	CKG 03 C	CKG 03 CN		

Compact 21.21 Inserts	Poles	Pages
CJ (RJ45)	1 A to 2,1 A	A.30-33
CUK (USB)	–	A.36
CX (BUS)	10 A	A.37
CLK (Fibre optics)	–	A.38

DESINA® version: suitable for DESINA® CJ, CUK, CLK, CX BD adapters for male inserts without gasket