

# C-TYPE series

## Hoods – 2 pegs – without gasket






size **104.27**
**Heavy-Duty  
Applications**


|                            |                    |
|----------------------------|--------------------|
| EN 60529                   | IP65 / IP66 / IP69 |
| UL 50 / UL 50E             | Type 12 / 4 / 4X   |
| Ambient temperature limits | -40 °C ... +125 °C |
| Mechanical life (cycles)   | ≥ 500              |

CE UK



ECBT2.E115072 | ECBT8.E115072

| Item                                                                                | Description                                                                                                            | Side entry                                                                                                           | Top entry                                                                                                            | Entry                        | Dimension                                                                                                       |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|------------------------------|-----------------------------------------------------------------------------------------------------------------|
|    | Hoods, 2 pegs, without gasket, side entry                                                                              | <a href="#">MHO 24 L25</a><br><a href="#">MHO 24 L32</a><br><a href="#">CHO 24 L</a>                                 |                                                                                                                      | M25<br>M32<br>Pg 21          | <br>138<br>68<br>43          |
|    | Hoods, 2 pegs, without gasket, top entry                                                                               |                                                                                                                      | <a href="#">MHV 24 L25</a><br><a href="#">MHV 24 L32</a><br><a href="#">CHV 24 L</a>                                 | M25<br>M32<br>Pg 21          | <br>120<br>138<br>68<br>43  |
|   | Hoods, 2 pegs, without gasket, side or top entry, high construction<br><br>To be used only with a complete cable gland | <a href="#">MFO 24 L32</a><br><a href="#">MFO 24 L40</a><br><a href="#">CFO 24 L21</a><br><a href="#">CFO 24 L29</a> | <a href="#">MFV 24 L32</a><br><a href="#">MFV 24 L40</a><br><a href="#">CFV 24 L21</a><br><a href="#">CFV 24 L29</a> | M32<br>M40<br>Pg 21<br>Pg 29 | <br>120<br>138<br>76<br>43 |
|  | Hoods, 2 pegs, without gasket, high construction, designed to be drilled                                               | Without entry<br><br><a href="#">CAC 24 L</a>                                                                        |                                                                                                                      |                              | <br>120<br>138<br>76<br>43 |

C-TYPE

E

| Inserts size 104.27 | Poles | Pages          | Inserts size 104.27 | Poles      | Pages                       | MIXO Modular Inserts               | Pages   |
|---------------------|-------|----------------|---------------------|------------|-----------------------------|------------------------------------|---------|
| CNE                 | 16 A  | 24 + ☉ B.41    | CSS                 | 16 A       | 24 + ☉ B.121                | MIXO modules                       | C.12-93 |
| CCE                 | 16 A  | 24 + ☉ B.47    | CMCE / CMSH         | 16 A       | 10 + 2 (aux.) + ☉ B.146,151 | CX 06 T (6-slot sized MIXO frames) | C.95    |
| CSH / JSH S         | 16 A  | 24 + ☉ B.55,61 | CX                  | 100 A/16 A | 8/0 and 6/6 + ☉ B.156-157   |                                    |         |
| CSHT                | 16 A  | 24 + ☉ B.68    | CX / CXC            | 80 A/16 A  | 4/8 + ☉ B.161-162           |                                    |         |
| CQE / CQEY          | 16 A  | 46 + ☉ B.75,85 |                     |            |                             |                                    |         |
| CQEE                | 16 A  | 64 + ☉ B.79    |                     |            |                             |                                    |         |
| CD                  | 10 A  | 64 + ☉ B.91    |                     |            |                             |                                    |         |
| CDD                 | 10 A  | 108 + ☉ B.97   |                     |            |                             |                                    |         |
| CDSH                | 10 A  | 42 + ☉ B.105   |                     |            |                             |                                    |         |

### Accessories:


**CHCP 24**  
Dust protection  
cover  
Page G.46