

E-Xtreme® – C-TYPE lever version

size **57.27**

Hoods and covers – 4 pegs – without gasket

2 000 hrs resistance
in salt-spray tests








Aggressive
Environments


EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 4 pegs, side entry, high construction To be used only with a complete cable gland	MFOE 10.32		M32	
	Hoods, 4 pegs, top entry, high construction To be used only with a complete cable gland		MFVE 10.32	M32	
	Covers, 4 pegs For enclosures with 2 levers and gasket with loop for hoods  or with eyelet for housings 	With loop CHCE 10	With eyelet CHCE 10 S		

E-Xtreme®

E

Inserts size 57.27	Poles	Pages	Inserts size 57.27	Poles	Pages		
CNE	16 A	10 + ☉	B.39	CMCE / CMSH	16 A	3 + 2 (aux.) + ☉	B.144,149
CCE	16 A	10 + ☉	B.45	CX	40 A/10 A	8/24 + ☉	B.170-171
CSH / JSH S	16 A	10 + ☉	B.53,59				
CSHT	16 A	10 + ☉	B.66				
CQE / CQEY	16 A	18 + ☉	B.73,83				
CDD	10 A	42 + ☉	B.95				
CDSH	10 A	18 + ☉	B.103				
CSS	16 A	10 + ☉	B.119				

Accessories:


CHCP 10
Dust protection
cover
Page G.46