

LS-TYPE series – Light and Sound

Housings, hoods and covers – 2 pegs – without gasket

size **44.27**Specialized
Applications






EN 60529	IP65
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +90 °C
Mechanical life (cycles)	≥ 500



CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, 2 pegs, without gasket	CHIN 06 LCH		
	Hoods, side entry, 2 pegs, without gasket	Side entry MHON 06 L25	M25	
	Hoods, top entry, 2 pegs, without gasket	Top entry MHVN 06 L25	M25	
	Hoods, side or top entry, 2 pegs, high construction, without gasket To be used only with a complete cable gland	Side entry MFON 06 L25 Top entry MFVN 06 L25	M25	
	Covers, 2 pegs, without gasket For enclosures with 1 lever and gasket with eyelet for housings 	CHCN 06 L		

Inserts size 44.27	Poles	Pages
CNE	16 A 6 + ⊕	B.38
CCE	16 A 6 + ⊕	B.44
CSH / JSH S	16 A 6 + ⊕	B.52,58
CQE / CQEY	16 A 10 + ⊕	B.72,82
CDD	10 A 24 + ⊕	B.94
CDSH / CDSH NC	10 A 9 and 6 + ⊕	B.102,108
CSS	16 A 6 + ⊕	B.118
CT / CTSE*	16 A 6 + ⊕	B.126,130

*can be used only in bulkhead mounting housings

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 02 T (2-slot sized MIXO frames)	C.95

dimensions shown in mm are not binding and may be changed without notice