LS-TYPE series – Light and Sound

size **57.27**

Housings, hoods and covers – 4 pegs – without gasket

Specialized Applications

EN 60529	**IP65**
UL 50 / UL 50E	**Type 12 / 4 / 4X**
Ambient temperature limits	**-40 °C ... +90 °C**
Mechanical life (cycles)	**≥ 500**

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.		Entry	Dimension
	Bulkhead mounting housings, 4 pegs, without gasket	**CHIN 10 CH**			
	Hoods, side entry, 4 pegs, without gasket	Side entry **MHON 10.25**		M25	
	Hoods, top entry, 4 pegs, without gasket		Top entry **MHVN 10.25**	M25	
	Hoods, side or top entry, 4 pegs, high construction, without gasket To be used only with a complete cable gland	Side entry **MFON 10.32**	Top entry **MFVN 10.32**	M32	
	Covers, 4 pegs, without gasket For enclosures with 2 levers and gasket with eyelet for housings 	**CHCN 10**			

Inserts size 57.27		Poles	Pages
CNE	16 A	10 + ⏚	B.39
CCE	16 A	10 + ⏚	B.45
CSH / JSH S	16 A	10 + ⏚	B.53,59
CSHT	16 A	10 + ⏚	B.66
CQE / CQEY	16 A	18 + ⏚	B.73,83
CDD	10 A	42 + ⏚	B.95
CDSH	10 A	18 + ⏚	B.103
CSS	16 A	10 + ⏚	B.119

Inserts size 57.27		Poles	Pages
CT / CTSE*	16 A	10 + ⏚	B.127,131
CMCE / CMSH	16 A	3 + 2 (aux.) + ⏚	B.144,149
CX	40 A/10 A	8/24 + ⏚	B.170-171

*can be used only in bulkhead mounting housings

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 03 T (3-slot sized MIXO frames)	C.95