

Central lever series

Housings and hoods with 2 pegs for central levers




size **44.27**Heavy-Duty
Applications

EN 60529	IP65
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, 2 pegs and gasket	CHI 06 YC		
	Surface mounting housings, 2 pegs and gasket, high construction, 2 entries	MAP 06 YC232 CAP 06 YC229	M32 × 2 Pg 29 × 2	
	Hoods, top entry, 2 pegs and gasket, high construction To be used only with a complete cable gland	MFV 06 GYC25 MFV 06 GYC32 MFV 06 GYC40 CFV 06 GYC21 CFV 06 GYC29	M25 M32 M40 Pg 21 Pg 29	

Inserts size 44.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE	16 A	6 + ⊕	B.38	
CCE	16 A	6 + ⊕	B.44	
CSH / JSH S	16 A	6 + ⊕	B.52,58	
CQE / CQEY	16 A	10 + ⊕	B.72,82	
CDD	10 A	24 + ⊕	B.94	
CDSH / CDSH NC	10 A	9 and 6 + ⊕	B.102,108	
CSS	16 A	6 + ⊕	B.118	
CT / CTSE*	16 A	6 + ⊕	B.126,130	

*can be used only in bulkhead mounting housings