

E-Xtreme® – C-TYPE lever version

Housings, hoods and covers – 2 levers – with gasket

size **77.62**

2 000 hrs resistance
in salt-spray tests



Aggressive Environments









EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK
CA



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, 2 levers and gasket	CHIE 32		
	Surface mounting housings, 2 levers and gasket	MHPE 32.50	M50	
	Hoods, 2 levers and gasket, top entry, high construction, with metal adapter	MHVE 32 G40	M40	
	Covers, 2 levers and gasket For enclosures with 4 pegs without gasket with loop for hoods 	CHCE 32 G		

Inserts size (77.27) × 2	Poles 	Pages
CNE 16 A	32 + ⊕	B.42
CCE 16 A	32 + ⊕	B.48
CSH / JSH S 16 A	32 + ⊕	B.56,62
CQE / CQEY 16 A	64 + ⊕	B.76,86
CD 10 A	80 + ⊕	B.92
CDD 10 A	144 + ⊕	B.98
CDSH 10 A	54 + ⊕	B.106
CP / CPY 35 A	12 + ⊕	B.113,115

Inserts size (77.27) × 2	Poles 	Pages
CSS 16 A	32 + ⊕	B.122
CTSE* 16 A	32 + ⊕	B.134
CMCE / CMSH 16 A	12 + 4 (aux.) + ⊕	B.147,152

*can be used only in bulkhead mounting housings

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 04 T (4-slot sized MIXO frames) × 2	C.95